

50/60 kW, 1000 Vdc String Inverters for North America

The CPS 50/60 kW three-phase string inverters are designed for ground mount, rooftop and carport applications. The units are high performance, advanced, and reliable inverters designed specifically for the North American environment and grid. High efficiency at 98.8% peak and 98.5% CEC, wide operating voltages, broad temperature ranges, and a NEMA Type 4X enclosure enable this inverter platform to operate at high performance across many applications.

The CPS 50/60KTL products ship with either the Standard wire box or the Rapid Shutdown wire box, each fully integrated and separable with touch-safe fusing, monitoring, and AC and DC disconnect switches. The integrated PLC transmitter in the Rapid Shutdown wire box enables PVRSS certified module-level rapid shutdown when used with APS RSD-S-PLC/RSD-D products. The CPS FlexOM Gateway enables monitoring, controls, and remote product upgrades.



CPS SCA50KTL-DO/US-480
CPS SCA60KTL-DO/US-480

Key Features

- PVRSS certified for rapid shutdown
- 55 & 66 kVA rating allows max rated active power @ ± 0.91 PF
- Selectable max. AC apparent power of 50/55 kVA and 60/66 kVA
- UL-1699B compliant arc-fault circuit protection
- 15-90° mounting orientation for low profile roof installs
- Optional FlexOM Gateway enables remote firmware upgrades
- Integrated AC and DC disconnect switches
- 3 MPPTs with 5 inputs each for maximum flexibility
- NEMA Type 4X outdoor rated enclosure
- UL 1741-SA certified to CA Rule 21, including SA8 - SA18
- UL 1741-SB and IEEE 1547-2018 certified
- Separable wire-box design for fast service
- Standard 10-year warranty with extensions up to 20 years



50/60KTL Standard Wire Box



50/60KTL Rapid Shutdown Wire Box

Model name	CPS SCA50KTL-DO/US-480		CPS SCA60KTL-DO/US-480
DC Input			
Max. PV power	90 kW (33 kW per MPPT)		
Max. DC input voltage	1000 Vdc		
Operating DC input voltage range	200-950 Vdc		
Startup DC input voltage / power	330 V / 80 W		
Number of MPPTs	3		
MPPT voltage range for Pnom @ PF>0.99	480-850 Vdc	540-850 Vdc	
Max. PV short circuit current ¹	163.2 A (54.4 A per MPPT)		
Number of DC inputs	15 inputs, 5 per MPPT		
DC disconnection type	Load-rated DC switch		
DC surge protection	Type II MOV		
AC Output			
Rated AC output power @ PF>0.99 to ±0.91 ²	50 kW	60 kW	
Max. AC apparent power (selectable ³)	50 / 55 kVA	60 / 66 kVA	
Rated output voltage	480 Vac		
Output voltage range ⁴	422-528 Vac		
Grid connection type	3Φ / PE / N (neutral optional)		
Max. AC output current @ 480 Vac	60.2 A (@ 50 kVA) / 66.2 A (@ 55 kVA)	72.2 A (@ 60 kVA) / 79.4 A (@ 66 kVA)	
Rated output frequency	60 Hz		
Output frequency range ⁴	57-63 Hz		
Power factor	>0.99 (±0.8 adjustable)		
Current TRD @ rated load	< 3%		
Max. fault current contribution (1 cycle RMS)	64.1 A (1.06/0.88 PU)		
Max. OCPD rating	125 A	125 A	
AC disconnection type	Load-break rated AC switch		
AC surge protection	Type II MOV		
System and Performance			
Topology	Transformerless		
Max. efficiency	98.8%		
CEC efficiency	98.5%		
Standby / night consumption	< 1 W		
Environment			
Enclosure protection degree	NEMA 4X		
Cooling method	Variable speed cooling fans		
Operating temperature range ⁵	-22°F to 140°F (-30°C to 60°C)		
Non-operating temperature range	-40°F to 158°F (-40°C to 70°C)		
Operating humidity	0-100%		
Operating altitude	13123 ft / 4000 m (derating from 9843 ft / 3000 m)		
Audible noise	<60 dBA @ 1 m and 77°F (25°C)		
Display and Communication			
User interface and display	LCD+LED		
Inverter monitoring	SunSpec, Modbus RS485		
Site-level monitoring	CPS FlexOM Gateway (1 per 32 inverters)		
Modbus data mapping	CPS		
Remote diagnostics / firmware upgrade functions	Standard / (with FlexOM Gateway)		
Mechanical			
Dimensions (H × W × D)	39.4 × 23.6 × 10.24 in (1000 × 600 × 260 mm)		
Weight	Inverter: 123.5 lb (56 kg) Wire box: 33 lb (15 kg)		
Mounting / installation angle ⁶	15 to 90 degrees from horizontal (vertical or angled)		
AC termination	M8 stud type terminal block (wire range: #6-3/0 AWG CU/AL; lugs not supplied)		
DC termination ⁷	Screw clamp, negative busbar (RSD version ⁷), wire range: #14-#6 AWG CU		
Fused string inputs (5 per MPPT)	RSD ⁷ and Standard wire box: 25 A fuses provided (fuse values up to 30 A acceptable)		
Safety			
Certifications and standards	UL 1741-SA/SB Ed. 3, UL 1699B, UL 1998, CSA-C22.2 NO.107.1-01, IEEE 1547-2018, FCC Part 15		
Selectable grid standards	IEEE 1547a-2014, IEEE 1547-2018 ⁸ , CA Rule 21, ISO-NE, HECO		
Smart-grid features	Volt-RideThru, Freq-RideThru, Ramp-Rate, Specified-PF, Volt-VAR, Freq-Watt, Volt-Watt		
Warranty			
Standard	10 years		
Extended terms	15 and 20 years		

1) The sum of parallel-connected PV module short-circuit currents.

2) Active power derating begins at PF = ± 0.91 to ± 0.80 when max AC apparent power is set to 55 or 66 kVA.

3) Inverters are factory set to 50 kVA and 60 kVA by default. Contact CPS to enable the higher kVA setting.

4) The "output voltage range" and "output frequency range" may differ according to the specific grid standard.

5) Active power derating begins at 40°C when PF = ± 0.9 and MPPT \geq Vmin; at 45°C when PF = 1 and MPPT \geq Vmin; and at 50°C when PF = 1 and MPPT \geq 700 Vdc.

6) Shade cover accessory required for installation angles of 75 degrees or less.

7) RSD wire-box only includes fuses and fuse holders on the positive polarity.

8) Firmware version 17.0 or later required.