

FIRST FLOOR PLUMBING  
DEMOLITION PLAN  
SCALE: 3/16"=1'-0"

## GENERAL NOTES

1. ALL PLUMBING ITEMS IN THIS BUILDING ARE TO BE REMOVED IN THEIR ENTIRETY, EXCEPT FOR THE ROOF & STORM DRAIN PIPING SYSTEM & THE VENT THROUGH ROOFS. THIS INCLUDES, BUT IS NOT LIMITED TO, DOMESTIC WATER PIPING, GAS PIPING, SANITARY WASTE AND VENT PIPING, HANGERS & SUPPORTS, VALVES, FLOOR DRAINS, WASTE RECEPTORS, GREASE INTERCEPTORS, WATER HEATERS & PLUMBING FIXTURES. ABANDON ANY UNDERSLAB PIPING IN PLACE. PROPERLY CUT & PATCH, TO MATCH EXISTING, AS NECESSARY FOR REMOVAL. THIS CONTRACTOR SHALL FIELD VERIFY EXTENT OF DEMOLITION WORK PRIOR TO BIDDING. MOST PIPING, EQUIPMENT & FIXTURES NOT SHOWN.

**Plumbing**  
A. CONTRACTOR SHALL BREAK OUT ALL COSTS ASSOCIATED WITH PIPING REVISIONS DUE TO THE "NEW DRIVE". SEPARATE FROM RENOVATIONS IN THE "NEW BEXLEY CITY HALL SPACE". LOCATED NORTH OF THE NEW DRIVE. THE SEPARATE COSTS SHALL INCLUDE: RELOCATION OF THE EXISTING GAS METERS FROM THE NORTH OF THE BUILDING TO THE SOUTH OF THE BUILDING, THE NEW GAS UTILITY TAP, NEW GAS PIPING ON THE ROOF TO THE EXISTING TENANT EQUIPMENT, DEMOLITION AT THE NEW DRIVE, NEW 1-1/2" DOMESTIC WATER SUPPLY PIPING, UNDERGROUND DOMESTIC WATER PIPING, AND THE HB-2 AT THE SOUTH SIDE OF THE NEW BEXLEY CITY HALL SPACE (SEE PD-1 AND PD-2 FOR ADDITIONAL DEMOLITION ITEMS ASSOCIATED WITH THE NEW DRIVE). NOTE THAT THE NEW DRIVE RENOVATIONS ARE NOT BEING BID AS AN ALTERNATE, BUT WILL BE COMPLETED AS PART OF THE BASE BID WORK. THE CITY IS REQUESTING THE BREAK OUT OF COSTS TO ASSIST IN THEIR REVIEW OF THE OVERALL PROJECT COSTS.

G | R

A | D


architects

330 W. Spring St, Suite 355  
Columbus, Ohio 43215  
614.228.2122

2631 Erie Avenue, Suite 25  
Cincinnati, Ohio 45208  
513.321.0444

### CONSULTANTS

Engineer  
Prater Engineering Associates Inc.  
6130 Wilcox Rd.  
Dublin, OH 43016



Bexley Square  
2232 East Main St.  
Bexley, Ohio  
43209

MARK	DATE	DESCRIPTION
△	08.03.14	Addendum 3
△	07.09.14	Addendum 2
△	07.07.14	Addendum 1
	05.01.14	Bid Set
	02.01.14	Commission Review

PROJECT NO: 1014-0001  
CAD FILE NAME: .  
DESIGNED BY: .  
DRAWN BY: .  
CHECKED BY: .  
COPYRIGHT: .

### SHEET TITLE

FIRST FLOOR  
PLUMBING  
DEMOLITION PLAN

PD-1-14105.DWG

**PRATER**  
Engineering Associates, Inc.

6130 Wilcox Road  
Dublin, Ohio 43016  
FAX: (614) 766 2354

DESIGNED BY MAW	DRAWN BY MAW	CHECKED BY SJM	JOB NUM. 14105
--------------------	-----------------	-------------------	-------------------


PD-1

# CODED NOTES

- EXISTING ROOF DRAIN TO REMAIN. PROVIDE NEW POLYPROPYLENE DOME. CLEAN OUT DRAIN ENTIRELY FROM ROOF LEVEL TO 5' OUTSIDE THE EXTERIOR BUILDING WALL TO ENSURE PROPER FULL DRAIN CAPACITY.
- EXISTING GAS SERVICE WITH METER BANK TO REMAIN IN ITS ENTIRETY.
- EXISTING GAS PIPING ON ROOF TO BE REMOVED INCLUDING PIPING SUPPORTS. CAP AT LOCATION INDICATED. FIELD VERIFY EXACT SIZE AND LOCATION.
- EXISTING VENT THRU ROOF TO REMAIN.
- EXISTING VENT THRU ROOF TO BE CAPPED AT BOTH THE UNDERSIDE OF ROOF STRUCTURE AND ON EXPOSED TOP SIDE OF VENT. VENT WILL NOT BE USED FOR REMODELED SPACE.
- EXISTING GAS DOWN THRU ROOF TO BE REMOVED. PATCH ROOF AS REQUIRED TO MATCH EXISTING.
- DISCONNECT GAS TO EXISTING ROOFTOP UNIT. COORDINATE EXACT LOCATION.
- EXISTING GAS PIPING ON ROOF TO ADJACENT TENANT ROOFTOP UNITS. DISCONNECT PIPING AND CAP AS NECESSARY FOR RECONNECTION TO NEW GAS PIPING COMING FROM SOUTH EAST CORNER. SEE SHT. P-3 FOR COORDINATION OF NEW WORK. REMOVE ALL PIPING NOT NEEDED FOR RECONNECTION WHEN NEW LINES HAVE BEEN INSTALLED.
- EXISTING GAS METER BANK FOR ADJACENT TENANTS TO BE REMOVED FOR RELOCATION. COORDINATE WITH COLUMBIA GAS. REMOVE ALL PIPING FROM METER BANK UP TO ROOF.

## Plumbing

A. Contractor shall break out all costs associated with piping revisions due to the "new drive" separate from renovations in the "new Bexley city hall space" located north of the new drive. The separate costs shall include: Relocation of the existing gas meters from the north of the building to the south of the building, the new gas utility tap, new gas piping on the roof to the existing tenant equipment, demolition of the new drive, new 1-1/2" domestic water supply piping, underground domestic water piping, and the HB-2 at the south side of the new Bexley city hall space (see PD-1 and PD-2 for additional demolition items associated with the new drive). Note that the new drive renovations are not being bid as an alternate, but will be completed as part of the base bid work. The City is requesting the break out of costs to assist in their review of the overall project costs.



**ROOF PLUMBING  
DEMOLITION PLAN**  
SCALE: 3/16"=1'-0"

G R

A D


architects

330 W. Spring St, Suite 355  
Columbus, Ohio 43215  
614.228.2122

2631 Erie Avenue, Suite 25  
Cincinnati, Ohio 45208  
513.321.0444

## CONSULTANTS

Engineer  
Prater Engineering Associates Inc.  
6130 Wilcox Rd.  
Dublin, OH 43016



**Bexley Square**  
2232 East Main St.  
Bexley, Ohio  
43209

△	08.03.14	Addendum 3
△	07.09.14	Addendum 2
△	07.07.14	Addendum 1
	05.01.14	Bid Set
	02.01.14	Commission Review

MARK	DATE	DESCRIPTION
------	------	-------------

PROJECT NO: 1014-0001  
CAD FILE NAME: .  
DESIGNED BY: .  
DRAWN BY: .  
CHECKED BY: .  
COPYRIGHT: .

## SHEET TITLE

ROOF  
PLUMBING  
DEMOLITION PLAN

PD-2

PD-2-14105.DWG


**PRATER**  
Engineering Associates, Inc.

6130 Wilcox Road  
Dublin, Ohio 43016  
FAX: (614) 766 2354

DESIGNED BY MAW	DRAWN BY MAW	CHECKED BY SJM	JOB NUM. 14105
--------------------	-----------------	-------------------	-------------------


WATER SERVICE NOTES:

1. WATER SERVICE ENTRANCE MATERIALS, INSTALLATION, AND ALL COMPONENTS (INCL'G. BUT NOT LIMITED TO METERS AND BACKFLOW PREVENTORS) TO BE IN ACCORDANCE WITH THE R.O.M.T.S. OF THE LOCAL WATER DEPT., VERIFIED IN ADVANCE OF ANY WORK.
2. ALL REDUCED PRESS. PRINCIPLE BACKFLOW PREVENTORS TO BE COMPLETE APPROVED ASSBY'S. INCL'G., BUT NOT LIMITED TO TEST COCKS AND AIR GAP FITTING AT VENT/DRAIN CONN. POINT. ASSBY'S. TO BE AS LISTED IN ASSE 1013, APPROVED BY THE LOCAL BACKFLOW PREVENTION AUTHORITY.
3. PROVIDE FLR. AND WALL SUPPORT ASSBY'S. AS REQ'D. TO SECURE AND SUPPORT ITEMS INDICATED AT STRUCT. PIPE STANDS EQUAL TO GRINNELL FIG. 62, WALL BRACKETS EQUAL TO GRINNELL FIG. 199.
4. THE PLUMBING CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING 3 COPIES OF A DETAILED ROUGH-IN WITH DIMENSIONS OF THE INSTALLATION OF THE METER AND BACKFLOW PREVENTER. COPIES TO BE GIVEN TO THE BEXLEY DIVISION OF WATER FOR REVIEW AND COMMENT. ALL COMMENTS FROM THE DIVISION OF WATER MUST BE INCORPORATED IN THE INSTALLATION.




DOMESTIC WATER SERVICE ENTRANCE DIAGRAM

NOT TO SCALE




WATERTIGHT FLOOR PENETRATION FOR PIPES

NOT TO SCALE




WATERTIGHT WALL PENETRATION FOR PIPES

NOT TO SCALE



TRAP PRIMER PIPING DIAGRAM


NOT TO SCALE



CO; OUTSIDE CLEANOUT DETAIL


NOT TO SCALE

FIXTURE SUPPLY SIZES		
FIXTURE	PEX PIPE SIZE	HW
WATER CLOSET	1"	---
LAVATORY	1/2"	1/2"
WATER COOLER	1/2"	---
WALL HYDRANTS	3/4"	---



TYPICAL PEX MANIFOLD PIPING DIAGRAM

NOT TO SCALE



SITE PLUMBING PLAN


SCALE: 1" = 20'-0"

330 W. Spring St, Suite 355  
Columbus, Ohio 43215  
614.228.2122

2631 Erie Avenue, Suite 25  
Cincinnati, Ohio 45208  
513.321.0444

CONSULTANTS

Engineer  
Prater Engineering Associates Inc  
6130 Wilcox Rd  
Dublin, OH 43016



Bexley Square  
2232 East Main St.  
Bexley, Ohio  
43209

MARK	DATE	DESCRIPTION
Δ	08.03.14	Addendum 3
Δ	07.09.14	Addendum 2
Δ	07.07.14	Addendum 1
	05.01.14	Bid Set
	02.01.14	Commission Review

PROJECT NO: 1014-0001

CAD FILE NAME: .

DESIGNED BY: .

DRAWN BY: .

CHECKED BY: .

COPYRIGHT: .

SHEET TITLE


SITE  
PLUMBING  
PLAN

P-0-14105.DWG

**PRATER**  
Engineering Associates, Inc.

6130 Wilcox Road  
Dublin, Ohio 43016  
(614) 766 4896  
FAX: (614) 766 2354

DESIGNED BY	DRAWN BY	CHECKED BY	JOB NUM.
MAW	MAW	SJM	14105




**FN** FIRST FLOOR  
PLUMBING PLAN  
SCALE: 3/16"=1'-0"

PLUMBING LEGEND			
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
CW	DOMESTIC COLD WATER LINE	OG	P-TRAP (PLAN VIEW)
D	DRAIN LINE	E	CAPPED LINE
G	GAS LINE (NATURAL)	H	HOSE BIBB
HW	HOT WATER LINE (DOMESTIC)	XG	PIPE BRANCH TOP CONNECTION
HW	HOT WATER RETURN (DOMESTIC)	+	PIPE BRANCH BOTTOM CONNECTION
IND	INDIRECT WASTE LINE	U	PIPE UNION
SAN	SANITARY LINE	Y	Y-TYPE STRAINER
STM	STORM LINE	CB	COMB. BALANCE & STOP VALVE
TP	TRAP PRIMER LINE	B	BALL VALVE
TW	TEMPERED WATER (DOMESTIC)	GV	GATE VALVE (SCREWED BODY)
V	VENT LINE	DV	DRAIN VALVE WITH HOSE END
W	WATER SERVICE LINE	CV	CHECK VALVE
180°	180°F WATER (DOMESTIC)	FAD	FLOOR OR AREA DRAIN
---	EXISTING WORK TO REMAIN	T	THERMOMETER
- - - -	EXISTING WORK TO BE REMOVED	CE	CONNECT TO EXISTING
		TF	THRU FLOOR AS SHOWN
		J	JANITOR OR SHOWER FAUCET/HEAD LOCATION

PLUMBING ABBREVIATIONS			
AB.	ABOVE	GEN.	GENERAL
A.F.F.	ABOVE FINISHED FLOOR	H.B.	HOSE BIBB
APPROX.	APPROXIMATELY	HTR.	HEATER
BTM.	BOTTOM	HTG.	HEATING
BLDG.	BUILDING	INV. ELEV.	INVERT ELEVATION
C.I.	CAST IRON	INT.	INTERIOR
CLG.	CEILING	LAV.	LAVATORY
CONC.	CONCRETE	MFR.	MANUFACTURER
C.O.	CLEAN OUT	MECH.	MECHANICAL
CONN.	CONNECT	PLBG.	PLUMBING
CONTR.	CONTRACTOR	PRESS.	PRESSURE
DTL.	DETAIL	REQD.	REQUIRED
DIA.	DIAMETER	R.D.	ROOF DRAIN
D.F.	DRINKING FOUNTAIN	RM.	ROOM
DN.	DOWN	S.D.	SHOWER DRAIN
D.S.	DOWNSPOUT	SH.	SHOWER
ELEC.	ELECTRICAL	S.S.	SERVICE SINK
E.W.C.	ELECTRIC WATER COOLER	T.P.	TRAP PRIMER
EXIST.	EXISTING	TYP.	TYPICAL
EXT.	EXTERIOR	UR.	URNAL
FLR.	FLOOR	V.T.R.	VENT THRU ROOF
F.D.	FLOOR DRAIN	W.	WASTE
FURN.	FURNISH	W/	WITH
F.V.	FLUSH VALVE	WC	WATER CLOSET

CODED NOTES		
1. 4" BUILDING SANITARY DRAIN TO 5'-0" BEYOND BUILDING PERIMETER FOR CONNECTION TO EXIST. UNDERGROUND SANITARY. FIELD VERIFY EXACT LOCATION AND INVERT ELEVATION OF EXIST. SANITARY PRIOR TO BEGINNING UNDERGROUND WORK.		
2. 1-1/2" CW SERVICE UP FROM BELOW SLAB. PROVIDE ASSE 1013, RPZ BACKFLOW PREVENTER, WATTS LF-009S. INSTALL PER OHIO PLUMBING CODE AND LOCAL AUTHORITY HAVING JURISDICTION REQUIREMENTS. SEE DIAGRAM ON SHEET P-0.		
3. ELECTRIC WATER HEATER, EWH-1, INSTALL PER WATER HEATER DIAGRAM ON SHEET P-3.		
4. 1/2" CW, 1/2" HW, 2" SAN & 1-1/2" VENT TO LAV.		
5. 1/2" & 4" SAN TO WATER CLOSET.		
6. 1/2" CW & 1/2" HW TO SHOWER VALVE.		
7. 1-1/4" CW DOWN IN WALL. EXTEND CW HEADER IN WALL AND PROVIDE 1/2" CONNECTIONS TO WATER CLOSETS & LAVS AND 3/4" CW TO URINAL. PROVIDE PDI SIZED "B" SHOCK ABSORBER PER PDI GUIDELINES.		
8. 1/2" CW, 2" SAN & 1-1/2" VENT TO ELECTRIC WATER COOLER.		
9. 1/2" CW, 1/2" HW, 2" SAN & 1-1/2" VENT TO SINK. EXTEND 1/2" CW BRANCH, WITH SEPARATE SHUTOFF VALVE, TO ICE MAKER BACKFLOW PREVENTER, EQUAL TO WATTS 007, EXPOSED IN CASEWORK. EXTEND BACK IN WALL AND RUN HORIZONTALLY TO WALL BOX.		
10. 3/4" CW DOWN IN WALL. EXTEND 1/2" CW TO ELECTRIC WATER HEATER, EWH-2, EXTEND 1/2" CW & 1/2" HW TO SINK. PROVIDE 1/2" CW BRANCH, WITH SEPARATE SHUTOFF VALVE & BACKFLOW PREVENTER (EQUAL TO WATTS SD-3) TO WATER FILTER ASSEMBLY, WF-1, UNDER SINK. ENSURE FILTERS CAN BE SERVICED AND INSTALL TO MAXIMIZE USABLE SPACE WITHIN CASEWORK. EXTEND CW LINE BACK IN WALL AND RUN HORIZONTALLY TO COFFEE MAKER. COORDINATE LOCATION WITH OWNER/ARCHITECT. INDIRECT BACKFLOW PREVENTER DRAIN PORT, FULL SIZE, TO HUB DRAIN IN CASEWORK WITH AIR BREAK. SEE DIAGRAMS ON SHEET P-3 FOR FURTHER DETAIL.		
11. CONNECT TO EXISTING VENT THROUGH ROOF AS HIGH AS POSSIBLE. VERIFY EXACT LOCATION IN FIELD. MAKE NECESSARY ADJUSTMENTS.		
12. PROVIDE TRAP PRIMER VALVE, TP-1, ABOVE CEILING IN THIS APPROXIMATE LOCATION. PROVIDE 1/2" CW TO INLET & EXTEND 1/2" TP SUPPLY TO DRAINS INDICATED ON PLANS. TP SUPPLY TO RUN CONCEALED IN STRUCTURE OR CASEWORK FOR EXTENSION & DISCHARGE TO DRAIN INLET.		
13. PROVIDE ALL SAW CUTTING FOR INSTALLATION OF UNDERSLAB SANITARY PIPING. PATCH TO MATCH EXISTING CONDITIONS.		
14. AT CONTRACTOR'S OPTION, PROVIDE PEX PIPING MANIFOLD ABOVE CEILING IN RESTROOM 104, AND EXTEND LINES TO EACH FIXTURE PER PEX MANIFOLD PIPING DIAGRAM ON SHEET P-0.		


P-1-14105.DWG			
<b>PRATER</b> Engineering Associates, Inc.			
6130 Wilcox Road Dublin, Ohio 43016		(614) 766 4896 FAX: (614) 766 2354	
DESIGNED BY MAW	DRAWN BY MAW	CHECKED BY SJM	JOB NUM. 14105



330 W. Spring St, Suite 355  
Columbus, Ohio 43215  
614.228.2122

2631 Erie Avenue, Suite 25  
Cincinnati, Ohio 45208  
513.321.0444


CONSULTANTS  
  
Engineer  
Prater Engineering Associates Inc.  
6130 Wilcox Rd.  
Dublin, OH 43016



**Bexley Square**  
2232 East Main St.  
Bexley, Ohio  
43209

MARK	DATE	DESCRIPTION
	08.03.14	Addendum 3
	07.09.14	Addendum 2
	07.07.14	Addendum 1
	05.01.14	Bid Set
	02.01.14	Commission Review
PROJECT NO: 1014-0001		
CAD FILE NAME: .		
DESIGNED BY: .		
DRAWN BY: .		
CHECKED BY: .		
COPYRIGHT: .		


SHEET TITLE  
FIRST FLOOR  
PLUMBING  
PLAN



**ROOF PLUMBING PLAN**  
SCALE: 3/16"=1'-0"

CODED NOTES ◻


1. NEW ROOFTOP UNIT BY OTHERS. PROVIDE NATURAL GAS CONNECTION AS INDICATED, WITH SHUTOFF VALVE, 6" MINIMUM DIRT LEG, UNION AND REDUCER (AS REQ'D). COORDINATE EXACT EQUIPMENT LOCATION, PRESSURE REQUIREMENTS AND GAS LOAD WITH EQUIPMENT PROVIDER. SEE PIPING DIAGRAM ON THIS SHEET.
2. CONNECT TO EXISTING GAS METER. EXTEND NEW PIPING UP TIGHT TO WALL TO ROOF.
3. EXISTING ROOF DRAIN TO REMAIN. CLEAN OUT DRAIN TO ENSURE PROPER FULL DRAIN CAPACITY.
4. PAINT GAS PIPING PER SPECIFICATIONS.




**R.T.U. GAS CONNECTION DIAGRAM**

GAS PIPING SUPPORT SPACING SCHEDULE			
PIPING TO BE SUPPORTED ACCORDING TO THE FOLLOWING SCHEDULE. SUPPORT AT INTERVALS NOT TO EXCEED SPACING LISTED OR ELSEWHERE AS REQUIRED IN ACCORDANCE WITH 2010 NFPA 54 AND 2006 INTERNATIONAL FUAL GAS CODE (IFGC).			
Steel Pipe		Steel Pipe	
Pipe Size	Spacing	Pipe Size	Spacing
1/2"	8'-0"	2"	10'-0"
3/4"	8'-0"	2-1/2"	10'-0"
1"	8'-0"	3"	10'-0"
1-1/4"	10'-0"	4"	10'-0"
1-1/2"	10'-0"		

INSTALLATION NOTE	
UTILIZE PRE-MANUFACTURED ROOF SUPPORT PRODUCT FOR PIPING. REMOVE ANY/ALL GRAVEL FROM UNDER SUPPORT. INSTALL SUPPORT AT SPACING PER ROOF SUPPORT SPACING SCHEDULE. SPACING OF SUPPORTS SHALL NOT EXCEED 10'-0". LONG PIPING RUNS MAY REQUIRE OVERSIZED CLAMPS OR ROLLERS TO ALLOW FOR EXPANSION AND CONTRACTION. INSTALL PER LOCAL CODES. INSTALL GAS PIPING LEVEL. PRESSURE TREATED WOOD IS NOT PERMITTED.	




**ROOFTOP GAS PIPE SUPPORT DETAILS**  
NOT TO SCALE  
EQUAL MANUFACTURERS: E-Z SLEEPER, MIRO INDUSTRIES, ROOFTOP BLOX



330 W. Spring St, Suite 355  
Columbus, Ohio 43215  
614.228.2122  
  
2631 Erie Avenue, Suite 25  
Cincinnati, Ohio 45208  
513.321.0444

CONSULTANTS  
  
Engineer  
Prater Engineering Associates Inc  
6130 Wilcox Rd  
Dublin, OH 43016



Bexley Square  
2232 East Main St.  
Bexley, Ohio  
43209

MARK	DATE	DESCRIPTION
△	08.03.14	Addendum 3
△	07.09.14	Addendum 2
△	07.07.14	Addendum 1
	05.01.14	Bid Set
	02.01.14	Commission Review

PROJECT NO:	1014-0001
CAD FILE NAME:	
DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
COPYRIGHT:	

SHEET TITLE  
ROOF PLUMBING PLAN

P-2-14105.DWG

**PRATER**  
Engineering Associates, Inc.

6130 Wilcox Road  
Dublin, Ohio 43016  
FAX: (614) 766 4896  
(614) 766 2354

DESIGNED BY MAW	DRAWN BY MAW	CHECKED BY SJM	JOB NUM. 14105
--------------------	-----------------	-------------------	-------------------







SPECIFICATIONS			
<div>GENERAL CONDITIONS</div> <div><div><div><div><div><div>1. EXCEPT AS SPECIFIED TO THE CONTRARY, THIS CONTRACTOR SHALL INCLUDE FURNISHING, INSTALLING, CONNECTING AND OPERATION OF ALL EQUIPMENT WHICH IS PART OF PLUMBING SYSTEMS.</div><div>2. GENERAL AND SPECIAL CONDITIONS OF AIA (AMERICAN INSTITUTE OF ARCHITECTS) AND OWNER'S GENERAL REQUIREMENTS SHALL APPLY UNLESS NOTED OTHERWISE.</div><div>3. THE REQUIREMENTS SET FORTH UNDER "GENERAL CONDITIONS", "MODIFICATIONS TO GENERAL CONDITIONS" AND "SPECIAL CONDITIONS" ARE PART OF THIS CONTRACT.</div><div>4. THIS CONTRACT SHALL INCLUDE A VISIT TO THE JOB SITE AND TAKE INTO CONSIDERATION MECHANICAL, ELECTRICAL AND GENERAL TRADE WORK IN PLACE AND TO BE DONE INTO OR AS PART OF THE PLUMBING CONTRACT. CONTROLS, PIPING, AND EQUIPMENT, AS REQUIRED TO MISS THIS WORK SHALL BE ACCOMPLISHED AT NO ADDITIONAL COST TO THE OWNER.</div><div>5. ALL MOTORS FOR SUCH EQUIPMENT (IF AND WHERE SPECIFIED ON THE DRAWINGS) SHALL BE FURNISHED AND INSTALLED AS PART OF THE PLUMBING CONTRACT. CONTROLS FOR SUCH MOTORS SHALL BE FURNISHED UNDER THIS CONTRACT AND INSTALLATION OF CONTROLS AND ALL ELECTRICAL WIRING NOT SHOWN ON ELECTRICAL DRAWINGS, SHALL BE PERFORMED UNDER THIS CONTRACT.</div></div></div><div><div><div>6. SUBSTITUTIONS AND MISCELLANEOUS EQUIPMENT</div><div>1. THE BIDDING OF THIS WORK WILL CONTEMPLATE THE USE OF EQUIPMENT AND MATERIALS EXACTLY AS SPECIFIED HEREIN, WHERE ONE OR MORE NAMES OF MANUFACTURERS ARE MENTIONED ANY ONE MAY BE UTILIZED.</div><div>2. ALTERNATE EQUIPMENT MAY BE BID AS A SUBSTITUTION TO THAT SPECIFIED WITH THE APPROPRIATE DEDUCT NOTED, HOWEVER, THE EQUIPMENT SUBSTITUTED SHALL MEET ALL SPECIFICATIONS IN DESIGN AND BE SUBJECT TO OWNER AND/OR ENGINEER APPROVAL. ANY ADDITIONAL COST INCURRED DUE TO SUBSTITUTION SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR AT NO EXPENSE TO THE OWNER.</div><div>3. MISCELLANEOUS ITEMS NECESSARY TO COMPLETE THE PIPING SYSTEMS SUCH AS FITTING, HANGERS, ETC., CAN BE BY ANY RECOGNIZED MANUFACTURER PROVIDED THESE ITEMS MEET MINIMUM STANDARDS OF THE PLUMBING CONTRACT ENGINEER.</div><div>4. ORDINANCES, PERMIT CERTIFICATES AND OWNER REQUIREMENTS.</div><div>5. ALL WORK UNDER THIS CONTRACT SHALL BE INSTALLED IN FULL ACCORDANCE WITH THE OWNER'S REQUIREMENTS, ALL LAWS, ORDINANCES AND ALL REGULATIONS OF THE STATE, COUNTY, AND MUNICIPALITY WHICH IN ANY WAY AFFECTS THIS WORK. THE ARCHITECT WILL OBTAIN THE GENERAL BUILDING, MECHANICAL, ELECTRICAL AND PLUMBING PERMITS AND THE NECESSARY PERMIT CERTIFICATES OF INSPECTION REQUIRED FOR THE PROJECT WILL BE OBTAINED BY THE CONTRACTOR PERFORMING THE WORK. FEES WILL BE INCLUDED IN THE BID PRICE. ALL WORK SHALL ALSO BE INSTALLED IN ACCORDANCE WITH REGULATIONS OF THE FIRE UNDERWRITERS ASSOCIATION AND LOCAL UTILITIES. THE CONTRACTOR SHALL ALSO SECURE ANY PERMITS OR PAY ANY FEES TO THE LOCAL UTILITY COMPANIES FOR THE WORK REQUIRED.</div></div></div><div><div><div>7. MECHANICAL DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED TO SHOW THE APPROXIMATE LOCATION OF OUTLETS, EQUIPMENT AND PIPING.</div><div>2. THE EXACT LOCATION OF PIPING, EQUIPMENT AND PIPING MAY BE CHANGED FROM TIME TO TIME AS WORK PROGRESSES. UNDER THIS CONTRACT ALL LOCATIONS SHALL BE VERIFIED WITH ALL TRADES AND THAT THEY ARE ACCORDING TO THE BEST INFORMATION AVAILABLE. SHOULD ANY CHANGES BE DONE THE WORK WILL BE CHANGED AT NO ADDITIONAL EXPENSE TO THE OWNER.</div><div>3. THE OWNER RESERVES THE RIGHT TO MAKE MINOR CHANGES IN LOCATION OF EQUIPMENT OF PIPING ARRANGEMENTS UP TO THE TIME OF ROUGH-IN WITHOUT ADDITIONAL COSTS TO THE OWNER.</div><div>4. THE DRAWINGS AND SPECIFICATION ARE INTENDED TO SUPPLEMENT EACH OTHER AND ANY MATERIALS OR LABOR CALLED FOR IN ONE SHALL BE FURNISHED EVEN THOUGH NOT MENTIONED IN BOTH ANY MATERIAL OR LABOR WHICH IS NOT SHOWN ON THE DRAWINGS NOR CALLED FOR IN THE SPECIFICATIONS BUT WHICH IS OBVIOUSLY NECESSARY TO COMPLETE THE WORK AND WHICH IS USUALLY INCLUDED IN WORK OF A SIMILAR CHARACTER SHALL BE FURNISHED UNDER THIS CONTRACT.</div><div>5. AS PART OF THIS WORK THE CONTRACTOR SHALL SUBMIT ONE (1) RED LINE SET OF AS BUILT DRAWINGS INDICATING THE EXACT LOCATION OF ALL WORK INSTALLED. ACCEPTANCE SHALL NOT OCCUR UNTIL RECEIPT OF THESE DRAWINGS IS OBTAINED BY THE OWNER.</div></div></div><div><div><div>8. SHOP DRAWINGS</div><div>1. AS PART OF THIS WORK INCLUDING UNDER EACH MECHANICAL SECTION, WITHOUT CAUSING ANY DELAY IN WORK, SHOP DRAWINGS OF ALL EQUIPMENT AND MATERIAL SHALL BE SUBMITTED FOR ENGINEER'S REVIEW.</div><div>2. SUBMITTAL SHALL INCLUDE WIRING DIAGRAMS, PERFORMANCE CURVES AND DATA SPECIFIC TO THIS PROJECT AND BEAR CONTRACTOR'S APPROVAL STAMP CERTIFYING THAT HE HAS VERIFIED CONFORMANCE TO THE CONTRACTUAL DOCUMENTS.</div><div>3. IN THE ENGINEER'S REVIEW IF SHOP DRAWINGS, REVIEW IS FOR CONFORMANCE WITH THE GENERAL DESIGN CONCEPT AND ARRANGMENT ONLY, COMMENTS, CORRECTIONS OR MARKING SO NOT CONSTITUTE WAIVER OF THE CONTRACT DOCUMENTS REQUIREMENTS, DIMENSIONS, QUANTITIES AND COORDINATION ARE THE RESPONSIBILITY OF THE CONTRACTOR.</div></div></div><div><div><div>9. CLEANING UP</div><div>1. UNLESS OTHERWISE NOTED, ALL EXCESS MATERIALS AND DEBRIS CAUSED BY THIS WORK SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND PROMPTLY BE REMOVED FROM THE SITE. ALL FIXTURES AND EQUIPMENT INSTALLED SHALL BE THOROUGHLY CLEANED WEEKLY. ALL MOTORS AND EQUIPMENT SHALL BE COVERED OR OTHERWISE PROTECTED FROM EACH BRANCH OF THE PLUMBING SYSTEMS. EQUIPMENT OTHER THAN THOSE DESIGNED TO ARE TO BE EXPOSED TO INCLEMENT WEATHER, TOUCH UP ALL SCRATCHES AND REPAIR ANY DENTS IN SPECIFIED.</div></div></div><div><div><div>10. CUTTING AND PATCHING</div><div>1. CUTTING FOR OPENINGS, WHEN NECESSARY, SHALL BE DONE BY THIS CONTRACTOR WITH SUCH TOOLS AND METHODS AS TO PREVENT UNNECESSARY DAMAGE TO SURROUNDING AREAS OR EQUIPMENT.</div><div>2. FILL SPACE IN ALL AREAS PACKING WHERE REQUIRED TO MAINTAIN FIRE RATING, OPENINGS SHALL BE TEMPORARILY FIRE STOPPED UNTIL PERMANENT FIRE STOPPING IS DONE. THIS INCLUDES HOLES LEFT DUE TO CUTTING OF PIPING.</div><div>3. PATCHING SHALL MATCH EXISTING SURFACES IN KIND AND FINISH, AND SHALL BE DONE BY THE GENERAL CONTRACTOR.</div><div>4. NO STRUCTURAL MATERIALS SHALL BE CUT INTO WITHOUT THE EXPRESSED PERMISSION OF THE OWNER'S REPRESENTATIVE.</div></div></div><div><div><div>11. FIRESTOPPING</div><div>1. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR FIRESTOPPING AROUND ALL OPENINGS FOR PIPES, DUCTS, ETC., AND THROUGH ALL WALLS AND ALL FIRE WALLS. FIRESTOPPING SHALL BE PERFORMED BY AN INSTALLER WHO HAS BEEN TRAINED BY THE MANUFACTURER, OR MANUFACTURER'S REPRESENTATIVE, IN THE INSTALLATION PROCEDURE. EACH CONTRACTOR SHALL BE RESPONSIBLE FOR FIRESTOPPING SHALL MEET THE REQUIREMENTS OF ASTM E-814 OR UL 1479 FIRE TESTS BY A RECOGNIZED TESTING AGENCY. FIRESTOPPING SHALL CONFORM TO THE FOLLOWING CODES: ASTM E-814, UL 1479, NFPA 70, NFPA 921, NFPA 101- LIFE SAFETY CODE &amp; NFPA 70 - NATIONAL ELECTRIC CODE.</div><div>2. PENETRATION</div><div>a. CLEAN PENETRATION HOLES OF DIRT, LOOSE MATERIALS AND FOREIGN MATTER WHICH MAY AFFECT BOIL OR INSTALLATION.</div><div>b. REMOVE COATINGS SUCH AS PAINT, CURE COMPOUNDS, WATER REPELLENT &amp; SEALERS AS WELL AS SEAL HOLES AND OPENINGS.</div><div>c. INSTALL BACKFILL MATERIALS TO PREVENT LIQUID MATERIAL LEAKAGE.</div><div>3. APPLICATION</div><div>a. PREPARE AND APPLY PENETRATION SEALING SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S PRINTED INSTRUCTIONS.</div><div>b. EMPLOY INSTALLATION TECHNIQUES WHICH WILL ENSURE THAT FIRESTOPPING IS DEPOSITED TO FILL AND SEAL HOLES AND OPENINGS.</div><div>c. TOOL EXPOSED SURFACES OF APPLIED SEALANT TO SMOOTH FINISH.</div><div>d. PROTECT MATERIALS FROM DAMAGE ON SURFACES SUBJECT TO TRAFFIC.</div><div>e. PROVIDE INTUMESCENT SEALANT AND COLLARS AT OPENINGS INVOLVING PLASTIC OR INSULATED PIPE SIMILAR TO THE METACALKU SERIES 880 AND 990.</div><div>4. FIRESTOPPING BY HILT, DOW CORNING, 3M, OR METACALKU MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</div></div></div><div><div><div>12. GUARANTEE</div><div>1. ALL LABOR AND MATERIALS FURNISHED UNDER THIS CONTRACT SHALL BE GUARANTEED FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE BY THE OWNER WHICH WILL COMMENCE UPON THE FINAL INSPECTION BY THE ENGINEER. DURING THIS TIME, THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FAILURES TO SUCH MATERIAL AND THE CORRECTION OF ALL DISCREPANCIES WITH THE PLUMBING CODE, THE CONTRACT DRAWINGS, AND THE PROJECT SPECIFICATIONS SHALL BE DONE UNDER THIS CONTRACT AT NO ADDITIONAL EXPENSE TO THE OWNER.</div></div></div><div><div><div>13. EXCAVATION AND BACKFILL</div><div>1. THIS CONTRACTOR SHALL EXCAVATE AND BACKFILL ALL TRENCHES AND OTHER EXCAVATIONS REQUIRED FOR LAYING DRAINS, SEWERS, APPURTENANCES AND OTHER EXCAVATIONS REQUIRED FOR HIS WORK.</div><div>2. EARTH FILL: SOIL AS APPROVED BY THE OWNER'S REPRESENTATIVE, FREE OF ORGANIC SOIL, SOD, ROOTS, WOOD, METAL, RUBBER, DEBRIS, LUMPS OR EXCESSIVE AMOUNTS OF CLAY AND ROCKS GREATER THAN 2" IN DIAMETER; CAPABLE OF BEING COMPACTED INTO DENSE AND STABLE CONDITIONS AS SPECIFIED.</div><div>3. ALL UNDERGROUND PIPING SHALL BE INSTALLED ON A MINIMUM OF A 3" BED OF COMPACTED SAND. ALL UNDERGROUND PIPING SHALL BE BACKFILLED BY HAND TO A LEVEL OF 6" ABOVE THE PIPE WITH CLEAN SAND. ALL BACKFILL SHALL BE MADE IN LIFTS NOT TO EXCEED 12". EACH LIFT SHALL BE MECHANICALLY COMPACTED TO A MINIMUM OF 92% MODIFIED PROCTOR.</div><div>4. PROTECT ALL UTILITIES SHOWN ON DRAWINGS OR ENCOUNTERED IN THE CONSTRUCTION WORK. ANY DAMAGE TO UTILITIES SHALL BE REPAIRED BY THIS CONTRACTOR TO OWNER'S SATISFACTION, WITHOUT COST TO THE OWNER.</div><div>5. THIS CONTRACTOR SHALL REMOVE ANY UNUSABLE OF SURPLUS EXCAVATED MATERIAL FROM THE SITE.</div></div></div><div><div><div>14. RECORD DRAWINGS</div><div>1. THIS CONTRACTOR SHALL KEEP AN ACCURATE RECORD OF ALL DEVIATIONS FROM CONTRACT DRAWINGS AND SPECIFICATIONS. HE SHALL NEATLY AND CORRECTLY ENTER IN COLORED PENCIL ANY DEVIATIONS ON THE DRAWINGS. AT COMPLETION OF THE PROJECT DELIVER DRAWINGS TO OWNER'S REPRESENTATIVE.</div></div></div><div><div><div>15. CONCRETE HOUSEKEEPING PAD</div><div>1. CONCRETE HOUSEKEEPING AND SUPPORT PADS FOR EQUIPMENT IN THE PLUMBING CONTRACT ARE THE RESPONSIBILITY OF THE PLUMBING CONTRACTOR. CONCRETE PAD CONSTRUCTION TO BE IN ACCORDANCE WITH SPECIFICATIONS PROVIDE IN THE GENERAL CONTRACT.</div></div></div></div><div><div><div><div>16. PLUMBING REFERENCES</div><div>A. APPLICABLE CONSTRUCTION CODES, STANDARDS AND GUIDELINES FOR ALL PLUMBING CONTRACT ELEMENTS, INCLUDING BUT NOT LIMITED TO THE FOLLOWING:</div><div>1. STATE OF OHIO, OHIO STATE BUILDING CODE, INCLUDING THE STATE OF OHIO PLUMBING CODE.</div><div>2. NATIONAL BUILDING CODE, INCLUDING PLUMBING, FUEL GAS, MECHANICAL, HANDICAP ACCESSIBILITY AND ENERGY CONSERVATION PORTIONS THEREOF.</div><div>3. LOCAL BOARD OF HEALTH.</div><div>4. AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME) STANDARDS FOR MATERIALS AND CONSTRUCTION.</div><div>5. NFPA PAMPHLET NO. 54, NATIONAL FUEL GAS CODE.</div><div>6. NFPA PAMPHLET NO. 70, NATIONAL ELECTRIC CODE.</div><div>7. CITY OF BEXLEY PUBLIC WORKS, UTILITIES DIVISION.</div><div>8. LOCAL GAS UTILITY PROVIDER'S CONTRACT COORDINATE INSTALLATION AND INTERFERE WITH THE PLUMBING CONTRACT.</div><div>9. AMERICAN GAS ASSOCIATION (AGA) STANDARDS FOR MATERIALS AND CONSTRUCTION.</div><div>10. AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME) STANDARDS FOR MATERIALS AND CONSTRUCTION.</div><div>11. AMERICAN SOCIETY OF SANITARY ENGINEERING (ASSE) STANDARDS FOR PERFORMANCE AND TESTING.</div><div>12. AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) STANDARDS FOR MATERIALS, CONSTRUCTION AND TESTING.</div><div>13. NATIONAL SANITATION FOUNDATION (NSF) STANDARDS FOR MATERIALS AND CONSTRUCTION.</div><div>14. CAST IRON SOIL PIPE INSTITUTE (CISPI) STANDARDS FOR MATERIAL AND CONSTRUCTION.</div><div>15. UNDERWRITER'S LABORATORIES (UL) STANDARDS FOR MATERIALS AND CONSTRUCTION.</div><div>16. THE MANUFACTURER'S INSTALLATION GUIDELINES AND RECOMMENDATIONS FOR INDIVIDUAL ITEMS, ELEMENTS AND/OR SYSTEM INDICATED HEREIN.</div></div></div><div><div><div>17. SCOPE OF WORK</div><div>A. THIS CONTRACTOR SHALL FURNISH ALL LABOR, MATERIALS, TOOLS, INCIDENTALS, DETAILS, ETC. NECESSARY TO PROVIDE A COMPLETE, OPERATIONAL AND APPROVED PLUMBING SYSTEM. THE PLUMBING CONTRACTOR SHALL BE RESPONSIBLE FOR ITEMS AND ELEMENTS DESCRIBED IN THE PLUMBING SPECIFICATION AND SHOWN ON THE PLUMBING DRAWINGS, AND AS REQUIRED FOR COORDINATION AND/OR INTERFACE WITH WORK UNDER SEPARATE CONTRACT AS INDICATED BY COMPLETE CONSTRUCTION DOCUMENTATION PAGE.</div><div>B. THE PLUMBING CONTRACTOR IS RESPONSIBLE FOR SATISFACTORILY ADDRESSING ALL REVIEW AND INSPECTION AUTHORITIES REQUIREMENTS AND DIRECTIVES IN REGARD TO METHODS OF INSTALLATION NECESSARY FOR FINAL APPROVAL.</div></div></div><div><div><div>18. PERMITS AND FEES</div><div>A. UNLESS DIRECTED OTHERWISE BY THE GENERAL CONDITIONS PORTION OF PROJECT DOCUMENTATION, THE PLUMBING CONTRACTOR SHALL APPLY FOR AND PAY ANY REVIEW INSPECTION, PERMIT, LICENSE, TESTING AND/OR OTHER SERVICE FEES REQUIRED BY ALL REVIEW/INSPECTION/ APPROVAL AUTHORITIES IN CONNECTION WITH THE WORK UNDER THIS CONTRACT.</div></div></div><div><div><div>19. PLUMBING UTILITY CONNECTIONS</div><div>A. PROVIDE PLUMBING SUPPLY, WASTE, DRAIN, VENT, AND ANY OTHER PIPED UTILITIES INCLUDED FOR THE PROJECT AS REQUIRED, AS LISTED HEREIN, AND/OR AS SHOWN ON THE PLUMBING DRAWINGS. THE PLUMBING CONTRACTOR SHALL BE RESPONSIBLE FOR SEPARATE CONTRACT REQUIRING SAME. THESE ITEMS SHALL INCLUDE, BUT NOT BE LIMITED TO THE FOLLOWING:</div><div>1. HVAC EQUIPMENT; FINAL CONNECTION ( WHERE APPLICABLE) BY THE HVAC CONTRACTOR.</div><div>2. EQUIPMENT FINAL CONNECTION (WHERE APPLICABLE) AS INDICATED BY PLAN NOTES.</div><div>3. OWNER PROVIDED ITEMS: FINAL CONNECTION (WHERE APPLICABLE) BY THE PLUMBING CONTRACTOR.</div><div>B. ROUGH-IN PLUMBING SUPPLY, WASTE, DRAIN, VENT, AND ANY OTHER PIPED UTILITIES INCLUDED FOR THE PROJECT AS REQUIRED, AS LISTED HEREIN, AND/OR AS SHOWN ON THE PLUMBING DRAWINGS FOR ALL FUTURE ITEMS REQUIRING SAME.</div></div></div><div><div><div>20. VALVE TAGGING AND CODING</div><div>A. PROVIDE BRASS TAGS ON ALL VALVES. TAGS SHALL STATE TYPE OF LINE IN WHICH THE VALVE IS INSTALLED (HOT WATER SUPPLY, STEAM, ETC.) AND NUMBER OF VALVE. FURNISH A SCHEDULE OR SCHEDULES OF ALL VALVES TAGGED WITH NUMBER, LOCATION, NUMBER OF EACH VALVE AND/OR VALVE SCHEDULES UNDER GLASS ON EQUIPMENT ROOM WALL, OR ELSEWHERE AS REQUIRED. SCHEDULES SHALL BE LOCATED NEAR AND CONVENIENT TO THE VALVES ON THE SCHEDULE.</div><div>B. PIPE TAGS SHALL BE STEEL AND VALVE TAG SCHEDULE - STENOLOG DESIGNATION</div><div>C. SERVICE</div><div>D. DOMESTIC COLD WATER</div><div>E. DOMESTIC HOT WATER</div><div>F. DOMESTIC HOT WATER RETURN</div><div>G. NATURAL GAS</div><div>H. BUILDING SANITARY</div><div>I. BUILDING STORM</div><div>J. IN THE CASE OF REMODELING WORK WHEN A VALVE IDENTIFICATION SYSTEM ALREADY EXISTS, NUMBERING SHALL START WITH THE NEXT NUMBER AFTER THE HIGHEST EXISTING NUMBER.</div><div>K. AFTER EXPOSED PIPING AND INSULATION IS PAINTED, THIS CONTRACTOR SHALL APPLY A STENOLOG LEGEND, LETTERED WITH THE NAME OF CONTENTS OF PIPING. THE FOLLOWING DIRECTION ARROWS OF THE IDENTIFICATION LEGENDS, SPACING NOT OVER 20" APART AND AT LEAST ONCE IN EACH ROOM. DO NOT USE ADHESIVE MARKERS. TYPE AND COLOR TO MATCH EXISTING TYPE AND COLOR TO BE APPROVED BY ENGINEER.</div><div>L. VALVE TAGS SHALL BE BRASS, MINIMUM 2" DIAMETER, 16 GAUGE.</div></div></div><div><div><div>21. PRODUCTS GENERAL</div><div>A. WHERE ITEMS/ELEMENTS ARE INDICATED HEREIN TO BE LISTED/APPROVED, THE INTENT OF THE SPECIFICATION IS THAT SAID ITEM/ELEMENT SHALL BE LISTED BY ALL APPLICABLE MATERIAL/CONSTRUCTION STANDARDS, AND SUBJECT TO FINAL APPROVAL (INCLUDING METHODS OF INSTALLATION) BY ALL REVIEW/INSPECTION/ APPROVAL AUTHORITIES.</div><div>B. UNLESS INDICATED OTHERWISE, ALL PLUMBING CONTRACT ITEMS/ELEMENTS (PIPE, FITTINGS, VALVES, SPECIALTIES, FIXTURES, EQUIPMENT, ETC.) MATERIALS, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, FURNISH COVER COMPLYING WITH THE FOLLOWING STANDARDS IN REGARD TO MATERIALS, CONSTRUCTION, DIMENSIONS/TOLERANCES, TYPE OF SERVICE/TRANSMISSION MEDIA (WATER, AIR, GAS, ETC.) AND METHODS OF INSTALLATION (AS APPLICABLE), AND SHALL BE SO LISTED. FINAL APPROVAL FOR USE IS SUBJECT TO THE REQUIREMENTS OF REVIEW AND INSPECTION AUTHORITIES:</div><div>1. STEEL PIPE, STEEL MALLEABLE AND CAST IRON FITTINGS AND JOINING METHODS; ASTM/ANSI/ASME/ASSE STANDARDS.</div><div>2. PLASTIC PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>3. CAST IRON PIPE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME/ASSE/NSF STANDARDS.</div><div>4. COPPER/COPPER ALLOY/BRASS PIPE/TUBE, FITTINGS AND JOINING METHODS; PER APPLICABLE ASTM/ANSI/ASME STANDARDS.</div><div>5. INSULATION, RATED FOR 180 DEGREES F, WITH A FACTORY APPLIED SELF-SEALING VAPOR BARRIER JACKET, BUT STRIPS SHALL BE MINIMUM 3" WIDE, AND OF SAME MATERIAL AS JACKET. EQUAL MATERIALS, INCLUDING THICKNESS AND CONDUCTIVITY RATINGS/LISTINGS, AS MANUFACTURED BY OWENS CORNING, KNAUF OR MANSON MAY BE FURNISHED, AT THE CONTRACTOR'S OPTION. WHERE INSULATION THICKNESS IS INDICATED FOR COVER HEREIN, IT IS NOMINAL THICKNESS REQUIRED THICKNESS.</div><div>6. LONGITUDINAL LAP JOINTS AND BUTT STRIPS FOR GLASS FIBER PIPING INSULATION SHALL BE SECURED WITH STAPLES ON THREE (3) INCH CENTERS, AND SEALED WITH AN APPROVED VAPOR BARRIER ADHESIVE WHERE APPLICABLE. STAPLES ARE NOT REQUIRED WHEN INSULATION UTILIZES A "DOUBLE" ADHESIVE SELF-SEALING SYSTEM.</div><div>7. INSULATION COVER, UNLESS THESE ASSEMBLIES ARE IN WATER SENSITIVE LOCATIONS, SUCH AS ABOVE LAY-IN CEILINGS, IF LISTED BACKFLOW PREVENTION ASSEMBLIES ARE IN WATER SENSITIVE</div></div></div></div></div></div>			



PLUMBING FIXTURE SCHEDULE				
PLUMBING FIXTURE NOTES:				
1. UNLESS INDICATED OTHERWISE, THE ARCHITECT SHALL SELECT THE FIXTURE COLOR/FINISH FROM THE MANUFACTURER'S FULL RANGE OF STANDARD OPTIONS.				
2. UNLESS INDICATED OTHERWISE, ALL EXPOSED METALLIC COMPONENTS TO BE FURNISHED WITH POLISHED CHROME FINISH, INCLUDING FAUCETS, TRAPS, STOPS, PIPING, ETC.				
3. UNLESS INDICATED OTHERWISE, ALL EXPOSED PIPING SHALL BE FURNISHED WITH POLISHED CHROME FINISH BRASS ESCUTCHEONS AT ALL WALL/CABINET PENETRATIONS AND FIXTURE CONNECTIONS.				
UR-1	AMERICAN STANDARD, SLOAN, ZURN	FIXTURE;	AMERICAN STANDARD WALL HUNG; WASHBROOK FLOWISE ULTRA HIGH EFFICIENCY, MODEL NO. 6590.001 (0.125 GPF).	3/4" ----
		CONTROLS;	SLOAN MANUAL OPERATED FLUSH VALVE, MODEL 186--0.125 GPF, 3/4" TOP SPUD INLET.	
		CARRIER;	ZURN SERIES 1221	




# SPECIFICATIONS

<p><b>SHOCK ABSORBERS</b></p> <p>A. SIMILAR TO ZURN SHOCKTROL SERIES 7-1700, SIZED AND INSTALLED AS RECOMMENDED BY THE MANUFACTURER FOR SPECIFIC CONDITIONS AT EACH LOCATION.</p> <p>B. EQUAL SHOCK ABSORBERS AS MANUFACTURED BY J.R. SMITH, JOSAM, SIOUX CHIEF OR PRECISION PLUMBING PRODUCTS MAY BE PROVIDED AT THE CONTRACTOR'S OPTION.</p> <p><b>TRAP PRIMER ASSEMBLIES</b></p> <p>A. SIMILAR TO SIOUX CHIEF PRODUCTS PRIME PERFECT SERIES 695 WITH BRASS BODY AND WORKING PRESSURE OF 250 PSIG. PROVIDE WITH DISTRIBUTION UNIT AS REQUIRED FOR MULTIPLE SUPPLIES TO FLOOR DRAIN. PROVIDE COPPER PIPING FROM TRAP PRIMER UNIT TO FLOOR DRAIN. TRAP PRIMER INLET.</p> <p>B. EQUAL TRAP PRIMER ASSEMBLIES AS MANUFACTURED BY ZURN, J.R. SMITH, JOSAM, PRECISION PLUMBING PRODUCTS, WADE, SLOAN, MIFAB OR SIOUX CHIEF MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</p> <p><b>PIPE ANCHORS, HANGERS AND SUPPORTS</b></p> <p>A. ALL PIPING SHALL BE SEPARATELY HUNG AND SUPPORTED FROM APPROVED STRUCTURAL MEMBERS OR CONCRETE OVERHEAD STRUCTURE ONLY. NO PIPE SHALL BE HUNG FROM ROOF DECK, PIPE DUCTS, OR OTHER COMPONENTS OR EQUIPMENT OF OTHER TRADES.</p> <p>B. PROVIDE LISTED/APPROVED ADJUSTABLE HANGERS, INSERTS, BRACKETS, CLAMPS, SUPPLEMENTAL STEEL AND OTHER DEVICES REQUIRED FOR PROPER SUPPORT OF ALL PIPE LINES.</p> <p>C. HANGERS SHALL BE DESIGNED TO ALLOW FOR EXPANSION AND CONTRACTION AND TO ALLOW INSULATION (WHERE APPLICABLE) TO RUN CONTINUOUSLY THROUGH HANGERS.</p> <p>D. WIRE OR STRAP HANGERS ARE NOT PERMITTED. ADJUST HANGERS SO AS TO DISTRIBUTE WEIGHT LOAD EQUALLY ON ATTACHMENTS.</p> <p>E. USE OF TRAPEZE HANGERS DO NOT PERMIT THE ELIMINATION OF THE PIPING INSULATION TO NOT BE CONTINUOUS THRU THE HANGER.</p> <p>F. PIPING TO BE SUPPORTED ACCORDING TO THE FOLLOWING SCHEDULE. SUPPORT AT INTERVALS NOT TO EXCEED SPACING LISTED OR ELSEWHERE AS REQUIRED IN ACCORDANCE WITH GOOD WORKMANSHIP. NO PIPE SHALL BE SUPPORTED FROM ANOTHER PIPE. ALL HANGERS SHALL BE PLUMBED BEFORE INSULATION IS APPLIED AND ALL HANGERS SHALL BE DOUBLE NUTTED. ALL HANGERS SHALL MEET THE OHIO PLUMBING CODE REQUIREMENTS.</p> <table><tr><th colspan="2">(1) Steel Pipe</th><th colspan="2">(2) Copper Pipe</th></tr><tr><th>Pipe Size</th><th>Spacing</th><th>Pipe Size</th><th>Spacing</th></tr><tr><td>Thru 1"</td><td>3/8"</td><td>Thru 3/4"</td><td>6'0"</td></tr><tr><td>1-1/4"</td><td>3/8"</td><td>1"</td><td>7'0"</td></tr><tr><td>1-1/2"</td><td>3/8"</td><td>1-1/4"</td><td>9'0"</td></tr><tr><td>2"</td><td>3/8"</td><td>2"</td><td>9'0"</td></tr><tr><td>2-1/2"</td><td>1/2"</td><td>2-1/2"</td><td>11'0"</td></tr><tr><td>3"</td><td>1/2"</td><td>3"</td><td>11'0"</td></tr><tr><td>4"</td><td>5/8"</td><td>4"</td><td>11'0"</td></tr><tr><td>6"</td><td>3/4"</td><td>6"</td><td>14'0"</td></tr><tr><td>8"</td><td>7/8"</td><td>8"</td><td>14'0"</td></tr></table> <p><b>DRAINS, CLEANOUTS, AND DRAINAGE SPECIALTIES</b></p> <p>A. GENERAL</p> <p>1. FURNISH AND INSTALL DRAINS, CLEANOUTS AND DRAINAGE SPECIALTIES AS INDICATED ON THE DRAWINGS, AND ELSEWHERE AS REQUIRED FOR COMPLETE DRAINAGE, ACCESS AND SPECIAL FUNCTION/OPERATION AT ALL ITEMS/ELEMENTS AND AREAS REQUIRING SAME AND FOR PROPER INTEGRATION WITH THE BUILDING DRAINAGE SYSTEM.</p> <p>2. UNLESS INDICATED OTHERWISE, ALL ITEMS/ELEMENTS AND THEIR COMPONENT PARTS DESCRIBED HEREIN TO BE OF METALLIC CONSTRUCTION WHEN SUCH IS AVAILABLE FOR THE BASE SPECIFIED ITEM/ELEMENT. USE OF PLASTIC, COMPOSITE, OR OTHER NON-METALLIC COMPONENTS AND/OR MATERIALS BY LISTED ALTERNATE ITEMS/ELEMENTS IS PROHIBITED.</p> <p>B. PRODUCTS</p> <p>1. HUB DRAINS TO CONSIST OF STRAIGHT SECTION OF HUB OR SOCKET TYPE CONNECTION WASTE PIPE INSTALLED IN THE VERTICAL POSITION, WITH THE HUB OR SOCKET PORTION EXPOSED ABOVE THE FLOOR. THE HUB INLET SHALL BE A MINIMUM OF 3" ABOVE THE FLOOR SURFACE. HUB OR SOCKET WASTE PIPE MATERIAL TO MATCH THAT OF THE SYSTEM IT IS CONNECTED TO.</p> <p>2. FURNISH AND INSTALL A P-TRAP FOR EACH SANITARY DRAIN INLET TERMINAL (FLOOR DRAIN, HUB DRAIN, FLOOR SINK, ETC.) OF THE SAME MATERIAL AND CONNECTION TYPE AS THE PIPING SYSTEM CONNECTED TO, UNLESS INDICATED OTHERWISE.</p> <p>3. THIS CONTRACTOR MAY, AT THEIR OPTION, USE ABS PLASTIC PLUGS IN LIEU OF BRONZE PLUGS WHERE SPECIFIED, EXCEPT ABS PLUGS SHALL NOT BE PERMITTED IN RETURN AIR PLENUMS OR AT EXPOSED LOCATIONS. LOCATION OF THE RETURN AIR PLENUM TO BE CONFIRMED WITH THE HVAC CONTRACTOR.</p> <p>4. ALL CLEANOUTS INSTALLED IN CARPETED AREAS TO BE PROVIDED WITH APPROVED VANDALPROOF CARPET MARKERS. CARPETED AREAS TO BE AS INDICATED BY ARCHITECTURAL DOCUMENTATION, AND CONFIRMED WITH THE GENERAL CONTRACTOR.</p> <p>5. CLEANOUTS IN TILE, MARBLE, TERRAZZO, PARQUET OR OTHER "SPECIAL" FLOOR TREATMENT AREAS TO BE PROVIDED WITH RECESSED TOPS TO ALLOW THE INTEGRATION WITH THE FLOOR TREATMENT. "SPECIAL" FLOOR TREATMENT AREAS TO BE AS INDICATED BY ARCHITECTURAL DOCUMENTATION, AND CONFIRMED WITH THE GENERAL CONTRACTOR.</p> <p>6. EQUAL DRAINS, DRAINAGE SPECIALTIES AND CLEANOUTS AS MANUFACTURED BY ZURN, JOSAM, WADE, WATTS OR J.R. SMITH MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</p> <p>C. EXECUTION</p> <p>1. WHEN TRAP PRIMER WATER SUPPLY IS INDICATED ON PLANS FOR DRAIN ASSEMBLIES, THE CONTRACTOR HAS THE OPTION TO CONNECT TO A FITTING ON EITHER THE DRAIN ASSEMBLY OR THE P-TRAP INLET ABOVE THE WATER SEAL, IN ACCORDANCE WITH INSPECTION/APPROVAL AUTHORITIES. PROVIDE A DIELECTRIC UNION AT TRAP PRIMER SUPPLY CONNECTION POINTS. WHEN DRAIN BODY PRIMER CONNECTIONS OCCUR WITHIN THE SLAB/FLOOR STRUCTURE, PROVIDE AN OFFSET IMMEDIATELY ADJACENT TO THE DRAIN LOCATION TO ALLOW INSTALLATION OF SUPPLY PIPING ENTIRELY BELOW THE SLAB/FLOOR STRUCTURE, INCLUDING THE CONDUIT SLEEVE REQUIRED FOR TRAP PRIMER SUPPLY PIPING UNDER SLAB ON GRADE.</p> <p>2. PROVIDE A COMPATIBLE FASTENING ASSEMBLY WITH INTERNAL SECONDARY DRAINAGE FLANGE AND WEEPHOLES FOR ALL ITEMS SPECIFIED HEREIN BEING INSTALLED IN STRUCTURES HAVING A WATER PROOF MEMBRANE, FLASHING, VAPOR BARRIER, OR SIMILAR ELEMENT PROVIDED UNDER SEPARATE CONTRACT. INSTALLATION CONDITIONS TO BE VERIFIED FROM ARCHITECTURAL DOCUMENTATION AND COORDINATED WITH THE APPROPRIATE CONTRACTOR.</p> <p>3. COUNTER FLASHING (WHEN REQUIRED) FOR ITEMS SPECIFIED HEREIN IS TO BE COMPATIBLE WITH WATERPROOF MEMBRANE, VAPOR BARRIER, FLASHING, OR SIMILAR ELEMENTS PROVIDED UNDER SEPARATE CONTRACT AT THE INTERFACE POINT. COUNTER FLASHING TO BE PROVIDED AND SET IN PLACE BY THE PLUMBING CONTRACTOR, BUT WILL BE MADE WATERTIGHT BY THE CONTRACTOR INSTALLING THE MEMBRANE, VAPOR BARRIER, FLASHING OR SIMILAR ELEMENTS PROVIDED UNDER SEPARATE CONTRACT. INSTALLATION CONDITIONS TO BE VERIFIED FROM ARCHITECTURAL DOCUMENTATION AND COORDINATED WITH THE APPROPRIATE CONTRACTOR.</p> <p>4. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR HAVING ALL DRAINS, CLEANOUTS AND OTHER ITEMS SO NOTED INSTALLED FLUSH AND LEVEL WITH FINISH WALL, FLOOR OR OTHER STRUCTURE AS APPLIES. COORDINATE INSTALLATION WITH CONTRACTOR'S PROVIDING ASSOCIATED STRUCTURE, INCLUDING REQUIRED ELEVATIONS AND DIMENSIONAL LOCATIONS. ITEMS NOT PROPERLY INSTALLED SHALL BE REMOVED AND REPLACED TO THE SATISFACTION OF THE OWNERS' ON-SITE REPRESENTATIVE.</p>	(1) Steel Pipe		(2) Copper Pipe		Pipe Size	Spacing	Pipe Size	Spacing	Thru 1"	3/8"	Thru 3/4"	6'0"	1-1/4"	3/8"	1"	7'0"	1-1/2"	3/8"	1-1/4"	9'0"	2"	3/8"	2"	9'0"	2-1/2"	1/2"	2-1/2"	11'0"	3"	1/2"	3"	11'0"	4"	5/8"	4"	11'0"	6"	3/4"	6"	14'0"	8"	7/8"	8"	14'0"	<p><b>PLUMBING FIXTURES</b></p> <p>A. GENERAL</p> <p>1. FURNISH AND INSTALL ALL PLUMBING FIXTURES AND ASSOCIATED ACCESSORIES AS SPECIFIED HEREIN AT LOCATIONS INDICATED ON THE DRAWINGS. FIXTURES TO BE PROVIDED FREE OF DEFECTS AND SET IN A NEAT, FINISHED AND UNIFORM MANNER.</p> <p>2. WHERE FIXTURES ARE INDICATED TO BE HANDICAP ACCESSIBLE, INSTALL AS DIRECTED HEREIN AND IN COMPLIANCE WITH THE CODES AND GUIDELINES REFERENCED.</p> <p>B. PRODUCTS</p> <p>1. PLUMBING FIXTURES, TRIM, FITTINGS, ACCESSORIES, APPURTENANCES, ETC. NOT INCLUDED HEREIN ARE AS SPECIFIED ON PLAN.</p> <p>2. CHINA PLUMBING FIXTURES AND ACCESSORIES AS MANUFACTURED BY AMERICAN STANDARD, KOHLER, ELJER, CRANE OR ZURN MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</p> <p>3. STAINLESS STEEL SINKS AND ACCESSORIES AS MANUFACTURED BY ELKAY, KOHLER, OR JUST MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</p> <p>4. EQUAL MANUAL OPERATION FAUCETS AND ACCESSORIES AS MANUFACTURED BY AMERICAN STANDARD, ELKAY, DELTA (COMMERCIAL), KOHLER, CHICAGO FAUCET, SPEAKMAN, ZURN OR T&amp;S BRASS MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</p> <p>5. SEATS FOR WATER CLOSETS AS MANUFACTURED BY REMIS, CHURCH, OLSONITE, BENEKE OR CENTAEO MAY BE FURNISHED AT THE CONTRACTOR'S OPTION. ALL SEATS ARE TO BE FURNISHED WITH SELF-SUSTAINING STAINLESS STEEL CHECK HINGES UNLESS NOTED OTHERWISE.</p> <p>6. EQUIVALENT PRECAST MOLDED STONE MOP SINK RECEPTORS AS MANUFACTURED BY FIAT, MUSTEE, SWAN, OR ZURN LC MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</p> <p>7. EQUIVALENT DISPOSERS/GARBAGE GRINDERS AS MANUFACTURED BY IN-SINK-ERATOR, WASTE KING, BUS BOY, EMERSON OR HOBART MAY BE FURNISHED AT THE CONTRACTOR'S OPTION.</p> <p>8. UNLESS INDICATED OTHERWISE, ALL EXPOSED METALLIC PARTS, PIPING, TRIM, FITTINGS, ACCESSORIES, APPURTENANCES, ETC., ASSOCIATED WITH PLUMBING FIXTURES SHALL BE POLISHED CHROME FINISH WHEN AVAILABLE. PROVIDE POLISHED CHROME PLATED BRASS ESCUTCHEONS ON PIPING AT ALL EXPOSED STRUCTURE PENETRATIONS (WALLS, FLOORS, CEILINGS, CASEWORK, ETC.) AND AT ALL FIXTURE CONNECTIONS.</p> <p>9. AT ALL HANDICAP ACCESS LAVATORIES AND/OR SINKS WITH EXPOSED SUPPLY AND DRAIN PIPING BELOW, PROVIDE PRE-FABRICATED CLOSED CELL VINYL INSULATION/COVER ASSEMBLIES WITH SEAMLESS PVC JACKET FOR ALL SUPPLY (FULL RANGE OF HOT, COLD AND TEMPERED) AND DRAIN PIPING. ASSEMBLY TO BE SIMILAR TO MCOURE PRO-WRAP SERIES, OFFSET DRAINS (IF USED) TO BE PROVIDED WITH COVER ASSEMBLIES SPECIFICALLY DESIGNED FOR SAME. ASSEMBLIES TO BE LISTED BY MANUFACTURER AS HANDICAP ACCESS COMPLIANT.</p> <p>C. EXECUTION</p> <p>1. PROVIDE INDIVIDUAL ACCESSIBLE STOP VALVES ON ALL FIXTURES AND EQUIPMENT SUPPLY PIPING.</p> <p>2. INSTALL ALL FIXTURES ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.</p> <p>3. MOUNTING HEIGHTS OF FIXTURES AS ASSOCIATED EQUIPMENT AS INDICATED ON DRAWINGS.</p> <p>4. INSTALL VANDAL RESISTANT 0.5 GPM FLOW RESTRICTIONS ON ALL LAVATORY FAUCETS IN PUBLIC ACCESS AREAS, SIMILAR TO CHICAGO FAUCET MODEL NUMBER E-2805.</p> <p>5. UNLESS NOTED OTHERWISE ALL WALL HUNG LAVATORIES SHALL BE SUPPORTED WITH A FLOOR MOUNTED CONCEALED ARM CARRIER, BOLT UNIT TO FLOOR.</p> <p>6. ALL EXPOSED PORTIONS OF SUPPLY AND DRAIN PIPING, INCLUDING FITTINGS, ACCESSORIES AND APPURTENANCES, BELOW HANDICAP ACCESS LAVATORIES AND SINKS (WITH THE EXCEPTION OF WALL ESCUTCHEONS) TO BE PROVIDED WITH COVER BY COMPLETED INSTALLATION SPECIFIED HEREIN, IN ACCORDANCE WITH HANDICAP ACCESSIBILITY REQUIREMENTS.</p> <p>7. AT ALL COUNTERTOP OR OTHER CASEWORK CONDITIONS, VERIFY EXACT LOCATION AND INSTALLATION OF ALL ITEMS WITH ARCHITECTURAL DOCUMENTATION BEFORE ANY WORK IS PERFORMED. COORDINATE INSTALLATION WITH THE GENERAL CONTRACTOR. WHERE PLUMBING FIXTURES ARE INSTALLED IN CASEWORK AND INDICATED TO BE "HANDICAP ACCESSIBLE", COORDINATE INSTALLATION WITH GENERAL CONTRACTOR TO PROVIDE CLEARANCES AND MOUNTING HEIGHTS AS REQUIRED.</p> <p>8. ALL HANDICAP ACCESS FIXTURE CONTROLS, INCLUDING FAUCETS AND FLUSH VALVES, TO BE PROVIDED WITH OPERATORS REQUIRING 5 POUND PRESSURE OR LESS FOR OPERATION.</p> <p>9. WHERE INDIVIDUAL FIXTURE SOLIDS INTERCEPTORS OR NEUTRALIZATION/DILUTION BASINS ARE INDICATED AT SINK LOCATIONS, INSTALL IN LIEU OF P-TRAPS SPECIFIED HEREIN, IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.</p> <p>10. WHERE ACCESSORIES SUCH AS GRAB BARS, SEATS, ETC., ARE PROVIDED BY THE GENERAL CONTRACTOR AT PLUMBING FIXTURE OR EQUIPMENT LOCATIONS (I.E. TOILET STALLS), COORDINATE INSTALLATION OF PLUMBING EQUIPMENT TO AVOID CONFLICTS, AND ALLOW PROPER OPERATION OF AND ACCESSIBILITY TO ALL ITEMS. VERIFY LOCATION OF ALL ITEMS PROVIDED BY THE GENERAL CONTRACTOR FROM ARCHITECTURAL DOCUMENTATION IN ADVANCE OF PLUMBING WORK BEING PERFORMED.</p> <p>11. WHEN SINKS ARE INDICATED ON THE DRAWINGS TO BE PROVIDED WITH DISPOSERS OR GARBAGE GRINDERS, DELETE SINK DRAIN ASSEMBLY SPECIFIED HEREIN, AS REQUIRED FOR DISPOSER/GRINDER INSTALLATION.</p> <p>12. SENSOR FAUCET TRANSFORMERS AND INTERCONNECTING FIXTURE WIRING AND ACCESSORIES TO BE LOCATED IN SECURE, RESTRICTED ACCESS AREAS/LOCATIONS (I.E. AND ACCESSIBLE CHASE, CASEWORK SUPERSTRUCTURE, ETC.). COORDINATE INSTALLATION WITH THE GENERAL CONTRACTOR.</p> <p>13. UNLESS INDICATED OTHERWISE, WHEN UNDER COUNTER TYPE DISHWASHERS ARE INSTALLED ADJACENT TO SINKS SPECIFIED HEREIN, PROVIDE 1/2" HOT WATER SUPPLY TO DISHWASHER FROM SINK SUPPLY UPSTREAM OF FIXTURE STOP, AND FURNISH P-TRAP WITH 1" DRAIN CONNECTION FITTING ON FIXTURE SIDE OF TRAP FOR DISHWASHER CONNECTION. DISHWASHER SUPPLY PIPING TO INCLUDE IN-LINE STOP, DUAL CHECK BACKFLOW PREVENTER (SIMILAR TO WATTS NO. 7) AND SHOCK ABSORBER. DISHWASHER PIPING BELOW COUNTER IN CASEWORK, IN A CONCEALED, ACCESSIBLE LOCATION. THE BACKFLOW PREVENTER IN THE SUPPLY PIPING MAY BE DELETED IF AN APPROVED BACKFLOW PREVENTION DEVICE IS CONFIRMED TO BE PROVIDED AS AN INTEGRAL COMPONENT OF THE DISHWASHER ASSEMBLY.</p> <p>14. JOINTS FORMED WHERE FIXTURES COME INTO CONTACT WITH WALLS OF FLOORS SHALL BE SEALED WATERTIGHT WITH AND APPROVED SEALING COMPOUND, COORDINATE INSTALLATION AND COLOR WITH THE GENERAL CONTRACTOR.</p>
(1) Steel Pipe		(2) Copper Pipe																																											
Pipe Size	Spacing	Pipe Size	Spacing																																										
Thru 1"	3/8"	Thru 3/4"	6'0"																																										
1-1/4"	3/8"	1"	7'0"																																										
1-1/2"	3/8"	1-1/4"	9'0"																																										
2"	3/8"	2"	9'0"																																										
2-1/2"	1/2"	2-1/2"	11'0"																																										
3"	1/2"	3"	11'0"																																										
4"	5/8"	4"	11'0"																																										
6"	3/4"	6"	14'0"																																										
8"	7/8"	8"	14'0"																																										

P-5--14105.DWG

<b>PRATER</b> Engineering Associates, Inc.			
6130 Wilcox Road Dublin, Ohio 43016		FAX: (614) 766 4896 (614) 766 2354	
DESIGNED BY MAW	DRAWN BY MAW	CHECKED BY SM	JOB NUM. 14105




330 W. Spring St, Suite 355  
Columbus, Ohio 43215  
614.228.2122

2631 Erie Avenue, Suite 25  
Cincinnati, Ohio 45208  
513.321.0444

CONSULTANTS

Engineer  
Prater Engineering Associates Inc  
6130 Wilcox Rd  
Dublin, OH 43016



Bexley Square  
2232 East Main St.  
Bexley, Ohio  
43209

	08.03.14	Addendum 3
	07.09.14	Addendum 2
	07.07.14	Addendum 1
	05.01.14	Bid Set
	02.01.14	Commission Review

MARK	DATE	DESCRIPTION
------	------	-------------

PROJECT NO: 1014-0001  
CAD FILE NAME: .  
DESIGNED BY: .  
DRAWN BY: .  
CHECKED BY: .  
COPYRIGHT: .

SHEET TITLE

PLUMBING  
SPECIFICATIONS  
CONTINUED