

CEILING SYMBOL LEGEND

HYAC SUPPLY

•	RECESSED CAN LIGHT		%" GYP. BOARD CEILING ® 9'-Ø" AFF, UNLESS NOTED
•	2' × 4' FLUORESCENT		OTHERWISE.
0	FLUORESCENT REFER TO ELECTRICAL FOR MOUNTING		AC-1 2'x4' ACOUSITCAL CEILING TILE @ 9'-Ø" UNLESS NOTED OTHERWISE.
	INDIRECT/DIRECT HUNG FLUORESCENT REFER TO ELECTRICAL FOR MOUNTING		AC-3
ı—o—ı	FLUORESCENT STRIP LIGHTING		2'x2' ACOUSITCAL CEILING TILE @ 9'-Ø" UNLESS NOTED OTHERWISE.
φ	WALL SCONCE- REFER TO INTERIOR ELEVATIONS/WALL SECTIONS FOR		DC-1 2'x2' SECURITY CEILING SYSTEM @ 9'-@" UNLESS NOTED OTHERWISE.
•	MOUNTING HEIGHTS		
Ф	PENDANT FIXTURE		DC-2 2' SECURITY CEILING PLANK
C	CLOSET LIGHT- FLUORESCENT		SYSTEM @ 9'-0" UNLESS NOTED OTHERWISE.
ΔΔ	TRACK LIGHTING		SECURITY CEILING ACCESS PANEL - COORDINATE
×	EXIT SIGN	AP	LOCATIONS WITH HYAC, PLUMBING & ELECTRICAL.

FIRST FLOOR
REFLECTED CEILING
PLAN

A 111