

AN ORDINANCE NO. 62

TO AMEND SECTION EIGHT OF AN ORDINANCE ENTITLED "AN ORDINANCE TO LICENSE SEWER BUILDERS AND TO PROVIDE RULES AND REGULATIONS FOR THE OPERATION OF THE SANITARY SEWER SYSTEM OF THE VILLAGE OF BEXLEY, FRANKLIN COUNTY OHIO."

Be it Ordained by the Council of the Village of Bexley, State of Ohio, as follows, to-wit:

Section 1.

That Section Eight of Ordinance No. 46 passed by the Council of the Village of Bexley Ohio, on the 21st day of December, 1913, entitled an ordinance "To License Sewer Builders and to Provide Rules and Regulations for the Operation of the Sanitary Sewer System of the Village of Bexley Franklin County, Ohio." be and hereby is amended to read as follows:

Section 8. All house sewers shall be constructed of vitrified sewer pipe of the bell and spigot pattern. The pipes shall be either standard pipe or of deep and wide socket dimensions and may be either in two or three foot lengths. All pipes shall be six inches in internal diameter and shall be true and straight and of first quality. The plumbing inspector shall have the right to reject all house sewer pipe which does not conform to these specifications.

Under no circumstances shall connections to the street sewers be made at points other than at the Y-connections provided by the Village in the street sewers, except under special permission and under special directions of the Village Engineer. Unless under special permission of the Village Engineer or Plumbing Inspector, all pipe shall be laid in open trench at a minimum slope of one quarter (1/4) inch per foot.

Joints shall be made with special care, using first a hemp gasket soaked in neat Portland cement and carefully caulked into the bell of the pipe. Upon the hemp gasket there shall be placed a mortar consisting of Portland cement one part and clean coarse sand two parts. The mortar shall extend around the pipe and shall be bevelled off for at least three inches. Special care shall be exercised to secure a good joint upon the

invert of the pipe.

Under special conditions, if required by the Village Engineer, house services shall be constructed of extra heavy cast iron soil pipe with lead joints.

The sewer trench between the sewer and the property line shall be carefully and thoroughly tamped in a workmanlike manner, or the material may be puddled as it is deposited in the trench or the entire trench may be flooded with water at the discretion of the Plumbing Inspector or that of the Village Engineer.

Section 2.

Section 8 of said Ordinance No. 46, passed ^{by} the council of said Village on the 23rd day of December, 1913, be and the same is hereby repealed.

Section 3.

THIS Ordinance shall take effect and be in force from and after the earliest period allowed by law.

Passed _____ 1914.

Mayor

Attest:

Clerk