



NOTES

1. REMOVE AND REPLACE ASPHALT PAVEMENT TO MATCH EXISTING AS APPROVED BY THE CITY OF BEXLEY.
2. USE HIGH STRENGTH CEMENT MORTAR RATED FOR EXTERIOR USE.
3. LIMITS OF REPAIR TO BE DETERMINED BY THE CITY OF BEXLEY.
4. ALL EXISTING BRICK SHALL BE SAVED AND REUSED.
5. SUPPLEMENTAL BRICK TO REPLACE BROKEN PAVERS SHALL BE SUBMITTED FOR APPROVAL TO THE CITY OF BEXLEY.
6. ALL WORK TO BE PERFORMED IN A PROFESSIONAL MANNER ALONG NEAT STRAIGHT LINES (INCLUDING ASPHALT REPAIR).
7. INSTALL BRICKS INTO WET MORTAR BED. EMBED EACH BRICK IN FRESH MORTAR INCLUDING JOINTS BETWEEN BRICKS.
8. INSTALL TOPSOIL, SEED AND MULCH BEHIND NEW CURB AFTER COMPLETION USING PULVERIZED TOPSOIL, PENN MULCH (OR APPROVED EQUAL) AND A BLUEGRASS, PERENNIAL RYEGRASS, FINE FESCUE MIX.

DATE: 11/18/20	BRICK CURB DETAIL	STANDARD CONSTRUCTION DRAWING	
	REPAIR OR REPLACEMENT	CITY OF BEXLEY, OHIO	BEX-ST-21